



MIDGET RULES

BODY

1. Any production based body kit. Vacuum formed or bent lexan/polycarbonate only.
2. Any minor modifications to the body must be approved before being allowed.
3. All corners should be rounded for safety

CHASSIS

1. Any 2WD production built conversion kit or 2WD purpose built chassis
2. Wheelbase Min 9.5" Max 10"
3. Width Min 8.5" Max 10"
4. Only non adjustable rear A arms are allowed. Trackside toe adjustable hubs are not allowed. Trackside adjustable wheelbase is not allowed.
5. RR may not be towed out
6. Offset - Right side of the cage may be no further offset from the outside of the RR tire than 3.625"
7. No weight may be added
8. Scale appearing contemporary cage made from rounded stock.

TRANSMISSION

1. 3 gear transmissions only
2. All gears must be full gears
3. No narrowed or lightened gears allowed
4. Plastic, Aluminum and Steel gears are permitted
5. Steel outdrives only
6. Blades are permitted
7. Ball diff only, No Gear Diffs Allowed

BATTERY

1. 2S Hard Case LiPo Battery only.

2. 8.44 volts MAX
3. Bullet connectors

MOTOR

1. Hobbywing Justock Speed Controller #30112003
2. Hobbywing 13.5 Justock #30408010

TIRES/WHEELS

1. Standard buggy 2.2 wheels
2. JConcept Sprinter or Quasi Speed Tires only

Rules may be changed or updated at any time. It is the participants responsibility to be up to date on the current rules.

Updated 3/5/2024