



## **MINI MUDBOSS**

### **BODY**

1. Any Mini Mudboss Body in Production (URCP, GT, Raptor, etc.)
2. Any minor modifications to the body must be approved before being allowed.

### **CHASSIS**

1. Stock Bandit or Rustler Chassis
2. Must have a rear bumper. RPM, Raptor or others are allowed.
3. Front bumper must be angled down.
4. Major alterations to the chassis modification to drivetrain/suspension component is not allowed.
5. Electronics must be installed within chassis surface and secured.
6. Mount for front body posts may be installed across the chassis. Must be secured and stable.

### **BATTERY**

1. 2 cell 7.4v LiPo battery with a maximum of 5200mah and 50c
2. External plug only no "Bullet Type" connectors

### **ADJUSTMENTS**

1. TRAXXAS 76/83/86/90 spur with all transmission parts in place (slipper)
2. Any pinion size
3. No modifications to transmission case
4. Traxxas grey and black hex hubs may be used in any combination
5. Transmission functionality rule (motor can not spin while slowly turning 1 rear wheel a full turn.)
6. Traxxas Steel transmission gears only (internal plastic transmission gears not allowed)
7. Adding weight (in any way) is not allowed.

## **BEARINGS**

1. Stock Bandit bushings may be replaced with bearings.
2. Bearing carriers may be replaced/upgraded with the Slash size bearing carriers to hold the larger 5x11x4 bearings.

## **SUSPENSION**

1. TRAXXAS 2WD plastic shocks only (grey or black) (fronts in front, rears in rear)
2. Original Springs only
3. Front springs may not be cut.
4. The shock's travel may be limited by using internal shims.
5. Original shafts in original cylinder (Length and type in proper cylinder)
6. Original pistons from kit only (1,2 or 3 hole) no modifications may be made
7. Stock camber bars only, no adjustable camber links

## **MOTOR**

1. Traxxas 12T Titan Brushed Motor with XL5 ESC.
2. OEM motor connectors only
3. Single 30mm fan may be used

## **TIRES/WHEELS**

1. Any buggy tire set may be used
2. Standard buggy wheels allowed
3. Additives/Prep allowed
4. Tire tread must show pattern (No slicks)

Rules may be changed or updated at any time. It is the participants responsibility to be up to date on the current rules.

Updated 3/5/2024